



Sales Rentals

Sales Service

Parts & Service



DeWalt D25323K Rotary Hammer

(ELESDS)



Product Features

- SHOCKS Active Vibration Control® Reduces vibration felt by the user at the handles. A Perform and Protect feature.
- 8 amp motor provides high performance and overload protection: 0-1,150 RPM, 0-4,300 BPM
- Variable speed trigger allows user to instantly control speed from 0 to dialed setting
- Delivers 2.5 ft lbs. of Impact Energy, providing fast drilling and powerful chipping
- Mode selector allows for usage in rotary hammer, rotary only, and chiseling applications
- Reversing feature helps release tool from bind up situations, and assists with removal of fasteners
- Integral clutch reduces sudden, high torque reactions if bit jams
- 360 degree side handle adjusts easily for preference or use in tight spaces
- Dust Extraction Connection allows the use of the D25300DH dust collection system

Specifications	
Optimal Concrete Drilling	5/32" - 5/8"
Amps	8.0Amps
Impact Energy	2.5ft-lbs
Vibration Control	Yes - SHOCKS
Vibration Measurement	10.5 m/s2
No Load Speed	0-1,150rpm
Blows/Min	0-4,300bpm
Chipping	Yes
Clutch	Yes
Wood/Steel Drilling	With adaptor"
Switch	vs
Tool Length	12.4"
Tool Weight	7.5lbs



DEWALL &