



PREMIER™ DUCTABLE UNIT HEATERS



Premier 80



Btu/h Rating				
Maximum	80,000			
Intermediate	-			
Ignition System	Direct Spark			
Heated Air Output (CFM)	450			
Dual Fuel Capability	-			
Fuel Consumption (max.)				
Liquid Propane Gas (lbs./hr.)	3.7			
Natural Gas (cu.ft/hr.)	80.0			
Inlet Gas Pressure				
Propane min./max. (in W.C.)	12.0/13.5			
Natural Gas min./max. (in. W.C.)	8.0/13.5			
Two Stage Output	No			
Electrical Supply (Volts/Hz/Phase)	115/60/1			
Amps (Starting /Cont. Oper.)	5.0/1.5			
Amps (15 amp circuit)	Yes			
Motor Horsepower	1/8			
Cabinet Material	Exclusive Tri-shield Coating**			
Wheels	-			
Fan Only Mode	S			
Dimensions (in.)				
Length	29.5			
Width	13.5			
Height	22.0			
Net Weight (lbs.)	70.0			
Shipping Weight (lbs.)	79.0			
Gas Pressure Regulator (with POL)	S			
Thermostat (Weatherproof with 20' cord)	S			
Gas Hose	15'			
Ducting*** (12" or 18" dia. x 12' length)	Gray-26346 Light Duty-26348			
CSA U.S. / Canada Certification	Yes			

*Amps spike over 15 during initial start-up. Check breaker capability

** Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

***Gray, White, and Light Duty ducts are Optional. Premier 80 and 170 require the 12" diameter duct, and the Premier 350 requires the 18" diameter duct. Part numbers listed. Duct part numbers differ on previously built models. Please call L.B. White for specific part numbers.

S=Standard O= Optional



World Provider of Innovative Heating Solutions