


Technical Specifications For Model SC-4 Extractor

Storage Dimensions / Weight:	Width: 12" Height: 25" Depth: 19.5" / 46 lbs.	
Construction:	High Impact Rotationally Molded Polyethylene, Cast Aluminum, Stainless Steel	
Recovery Tank:	4 Gal. Built-In Removable Easy Pour Recovery Tank for Filling & Emptying	
Solution Tank:	4 Gal. with Pump Protecting Dual Filtration	
Solution Tube:	Solution Level-Drain Tube for User Convenience	
Handle:	Four Position Adjustable and Collapsible for Storage and Transport	
Vacuum Lid:	Hinged, Dual Sight Glass, Protective Vacuum Filter	
Vacuum Motor:	Ametek High Performance Two-Stage / 108" Water Lift / 112 CFM	
Pump:	35 PSI / .85 GPM	
Brush Motor:	2,500 RPM Permanent Magnate DC	
Brush:	1,200 RPM Three Row Chevron, Stainless Shaft, Shock Mounted Bearings	
Brush Housing:	Heavy Duty Cast Aluminium, Stainless Bearings, Kevlar Reinforced Gear Belt	
Vacuum Nozzle:	Heavy Duty Cast Aluminum, with Stainless or Delrin Glide for Hard Surface	
Instructions:	Easy to Read Operating Instructions Printed on the Machine	
Accessories:	Vacuum and Pump Accessory Ports for Hand Tools and Floor Wands	
 USER SAFETY Conforms To UL STD 1017 And CSA STD C22.2 No. 243-01	Self-contained carpet extractors feature a high speed chevron brush to loosen ground in soil. The brush works on types of carpets with no adjustment required. Well balanced rotational molded polyethylene construction for ease of operation and years of reliable top performance.	Optional Quick Dry and Dual Surface Cleaning: Uses Less Water Dries Fast Less Emptying & Refilling



Heavy Duty Cast Aluminum Vacuum Nozzle and Brush Housing with Powerful Chevron Brush



Made with pride in the U.S.A.