



FORCE/2 HP

Intec Part #:
K20022 F2w/wired remote
K20022 F2 GW w/wireless remote
Insulation Blowing Machine

FORCE/2 HP



Professional Grade – High Performance to meet Contractors’ Demands



Easy to find power: 2-15amp 115V circuits

1 for blower, 1 for agitator

High pressure provides fast & efficient dense pack

Powerful 2-stage blower & one-way valve provides many capabilities with high volume, high pressure, and long-life

Twist-Lock electrical receptacles

Hold cord in place

Use with Intec’s heavy duty 12/3 power cords or your own

High Production*

- Cellulose: 30 – 40 lbs per min
- Fiberglass: 9 – 11 lbs per min

**testing per ASTM C519 standards.*



System shown with standard heavy duty wired remote & industry exclusive urethane jacketed controls for enhanced durability

Intec’s **FORCE/2 HP** comes with these industry leading components on which it has built its reputation for durability and reliability:

- ✓ **Polyethylene construction:** rust-free, lightweight, and extremely durable.
- ✓ **Intec’s urethane seals:** last 2-3X longer than industry standard providing higher pressures & increased production rates over longer periods of time with less maintenance.
- ✓ **Stainless steel airlock plates:** provide long wear life vs. industry standard airlock construction.
- ✓ **Direct-drive transmission:** fewer moving parts provides longevity with little maintenance.

*integrity
trust*

excellence

innovation

www.inteccorp.com

Click pictures for website link

Rev: 20210329

Intec’s Professional Grade Equipment

Engineered for High Productivity

Built-to-Last for High Value Generation

FORCE®

Insulation Blowing Machines



Specifications



- Weight: 260lbs (118kg) 77cm
- Transmission: Durable direct drive – no chains
- Hose outlet: 3 inches (7.6cm)
- Electrical: 115VAC – 2 -15amp circuits required
- Blower: 115 VAC – 15 amp input, two-stage with one way valve
- Agitator motor: 115VAC-15amp input
- Hopper: 9 cubic feet (13 with hopper extension)
- Warranty: 1 year, limited

Specifications subject to change; contact Intec for current specifications

Accessories



Kits for Dense Pack, Blow Behind Netting, and Spray-on



Hopper Extension



Wheel Kit



Swivel hose connectors & hose kits



- ✓ Wired Remote standard with *Intec Exclusive* impact resistant Urethane head. 
- ✓ Long lasting Blower: Infinity brush technology with one-way valve to prevent insulation from coming into contact with blower combine to provide exceptionally long life.
- ✓ GOWIRELESS: Industrial Grade Wireless transmitter (optional) comes with four placement options.
 -  Jacket for Wrist or Hose
 -  Lanyard
 -  Lanyard
 -  Belt Clip
- ✓ Polyethylene construction: rust-free, lightweight, and extremely durable – will not dent.
- ✓ Urethane seals: last 2-3X longer than belted rubber providing higher pressures & production rates over time with less maintenance. 
- ✓ Stainless steel airlock plates: provide long wear life vs. industry standard airlock construction.
- ✓ Direct-drive transmission: Fewer moving parts w/ no chains provides longevity with minimal maintenance.

Backed by Intec's industry leading Technical Service. Training & Accessories are available to increase your efficiencies.

Distributed by



Manufactured by

Insulation Technology Corporation, d.b.a. Intec
9251 Bruin Boulevard
Frederick, CO 80504

Click pictures for website link 



Local: 303-833-6644
Fax: 303-833-6650
sales@inteccorp.com

www.inteccorp.com

... it's the 'tec' inside that counts!

