

V20 MINI SKID STEER RAIL PALLET FORK

Available widths 36" & 42"

Adjustable ITA Class II forged tines.



36.0" FRAME WIDTH	2200 LB CAPACITY	36" & 42" TINE LENGTHS	< 1650 LB LOADER OPERATING CAP.
--------------------------	-------------------------	-----------------------------------	---

1. 3/16" BRICKGUARD & 3/4" BEVELED RAIL
2. BRICKGUARD FLUSH WITH TINES TO HELP STABILIZE LOADS

CHOOSE MINI SKID MOUNT:

- TORO®/MINI UNIVERSAL
- BOBCAT®
- ASV®
- Universal skid steer quick tach mount not available.

MODEL	CPF3622	CPF4222
Width: Frame / Overall w/Step (in.)	36.0	
Overall Height (in.)	30.1	
Tine: Length / Width / Thickness (in.)	36.0 / 3.0 / 1.19	42.0 / 3.0 / 1.19
Tine Space: Min / Max (in.)	8.4 / 30.9	
Approximate Weight (lbs)	245	255
Capacity (lbs)	2200	
Recommended Loader Capacity	Less than 1650 lbs	

V20 MINI SKID WIDE RAIL PALLET FORK

Available widths 36" & 42"

Wider rail for better stability and adjustable ITA Class II forged tines.



42.0" FRAME WIDTH	2200 LB CAPACITY	36" & 42" TINE LENGTHS	< 1650 LB LOADER OPERATING CAP.
--------------------------	-------------------------	-----------------------------------	---

1. 3/16" BRICKGUARD & 3/4" BEVELED RAIL
2. BRICKGUARD FLUSH WITH TINES TO HELP STABILIZE LOADS
3. ASV® PALLET FORK INCLUDES BOLT-ON STEP

CHOOSE MINI SKID MOUNT:

- TORO®/MINI UNIVERSAL
- BOBCAT®
- ASV®
- Universal skid steer quick tach mount not available.

MODEL	CWPF3622	CWPF4222
Width: Frame / Overall w/Step (in.)	42.0 / 47.0	
Overall Height (in.)	30.1	
Tine: Length / Width / Thickness (in.)	36.0 / 3.0 / 1.19	42.0 / 3.0 / 1.19
Tine Space: Min / Max (in.)	8.4 / 37.6	
Approximate Weight (lbs)	265*	275*
Capacity (lbs)	2200	
Recommended Loader Capacity	Less than 1650 lbs	

*Bobcat® & ASV® models weigh approximately 5 lbs less.