

L.B.WHITE**TRADESMAN®
FORCED AIR HEATERS**

| TRADESMAN® | 125 | 170 | 170 ULTRA | 170N | 170N ULTRA | 400 | 400 ULTRA | 400 ULTRA DF |
|--|----------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| BTU/H RATING | 70,000-125,000 | 125,000-170,000 | 125,000-170,000 | 125,000-155,000 | 125,000-155,000 | 250,000-400,000 | 250,000-400,000 | 175,000-400,000* |
| HEATED AIR OUTPUT (CFM) | 400 | 550 | 550 | 550 | 550 | 1,050 | 1,050 | 1,050 |
| FUEL TYPE | LP | LP | LP | NG | NG | LP | LP | LP/NG |
| FUEL CONSUMPTION LP GAS MIN./MAX. (LBS./HR.) | 3.2 / 5.8 | 5.8 / 7.9 | 5.8 / 7.9 | - | - | 11.6 / 18.6 | 11.6 / 18.6 | 11.6 / 18.6 |
| FUEL CONSUMPTION NAT. GAS MIN./MAX. (CU.FT./HR.) | - | - | - | 125 / 155 | 125 / 155 | - | - | 175 / 400 |
| INLET GAS PRESSURE LP GAS | 11.0 (IN. W.C.) | 11.1 (IN. W.C.) | 11.1 (IN. W.C.) | - | - | 5.2 PSIG | 5.2 PSIG | 1.5 PSIG |
| INLET GAS PRESSURE NAT. GAS MIN./MAX. | - | - | - | 7/13.5 (IN. W.C.) | 7/13.5 (IN. W.C.) | - | - | 1.5 PSIG |
| AMPS (STARTING/CONTINUOUS OPERATION) | 2.0 / 0.70 | 3.7 / 1.0 | 3.7 / 1.0 | 3.7 / 1.0 | 3.7 / 1.0 | 4.0 / 1.3 | 4.0 / 1.3 | 4.0 / 1.3 |
| SERVICE SAVER (SELF-DIAGNOSTICS) | - | - | YES | - | YES | - | YES | YES |
| LENGTH (IN.) | 25.6 | 24.0 | 24.0 | 24.0 | 24.0 | 34.5 | 34.5 | 34.5 |
| WIDTH (IN.) | 11.8 | 9.5 | 9.5 | 9.5 | 9.5 | 12.5 | 12.5 | 12.5 |
| HEIGHT (IN.) | 16.0 | 16.0 | 16.0 | 16.0 | 16.0 | 21.5 | 21.5 | 21.5 |
| SHIPPING WEIGHT (LBS.) | 28.0 | 34.0 | 34.0 | 34.0 | 34.0 | 51.0 | 51.0 | 55.0 |
| CASE MATERIAL | STEEL W/BAKED ENAMEL | STEEL W/ TRI-SHIELD COATING** | STEEL W/ TRI-SHIELD COATING** | STEEL W/ TRI-SHIELD COATING** | STEEL W/ TRI-SHIELD COATING** | STEEL W/ TRI-SHIELD COATING** | STEEL W/ TRI-SHIELD COATING** | STEEL W/ TRI-SHIELD COATING** |
| HIGH TEMP SAFETY SWITCH | YES | YES | YES | YES | YES | YES | YES | YES |
| AIR FLOW SAFETY SWITCH | NO | NO | YES | NO | YES | YES | YES | YES |
| GAS PRESSURE REGULATOR | S (W/POL) | S (W/POL) | S (W/POL) | S | S | S (W/POL) | S (W/POL) | S (W/POL) |
| UNIT MOUNT THERMOSTAT | *** | S | S | S | S | S | S | S |
| GAS HOSE | S | S | S | O | O | S | S | S |
| CSA CERTIFICATION | US & CANADA | US & CANADA | US & CANADA | US & CANADA | US & CANADA | US & CANADA | US & CANADA | US ONLY |

S=Standard O=Optional

*250,000 to 400,000 on LP.

** Tri-shield coating consists of 3 unique protective layers: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer, and a baked, thermosetting polyester.

***Thermostat not available due to configuration of gas train.

TWO YEAR WARRANTY

CA RESIDENTS:

Cancer and reproductive harm. See
www.P65Warnings.ca.gov.**WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS**411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com **MADE IN USA**
OF U.S. & IMPORTED PARTS© 2017 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.