



Click Here To View
Item at

www.GapPower.com


*Sales • Rentals
Parts & Service*



LITTLE BEAVER®
EARTH DRILLS & AUGERS

MECHANICAL EARTH DRILLS

- Lightweight, powerful, reliable
- High speed auger rotation digs holes quickly and cleanly
- Torque-free digging eliminates kickback



Applications:

- Fencing
- Decks
- Landscaping
- Sign erection
- Soil sampling
- Horizontal boring

Mechanical Earth Drills

COMPLETE LINE OF ONE-MAN EARTH DRILLS, AUGERS AND MINI-TRENCHERS






For over 40 years, the versatile Little Beaver mechanical earth drill has been the #1 choice of rental store owners, fencing contractors, and other professionals who require a one-man auger that is safe and simple to operate. Thanks to our patented torque tube, we've eliminated the kickback found in competitive augers, making one-man drilling safe and productive.

Little Beaver's horizontal boring options easily convert your earth drill into a cost effective horizontal boring machine. The sidewalk auger kit uses a 3" auger and wiggle joint extension to bore up to 5'. The water drilling kit is used for horizontal distances up to 50' with a diameter of 2, 3, or 4".

ENGINEERED TO WORK...AND TO LAST



We build our own heavy-duty transmissions that feature cooling fins for quick heat dissipation, o-ring seals, and heat-treated shafts and bearings mounted in an oil bath.



The engine throttle control and the on/off switch are conveniently located on the left handle. Padded handles are ergonomically designed for less fatiguing operation.



A reliable, centrifugal clutch slips when a buried object is encountered or the auger is overloaded. This protects the flexible drive cable and the transmission gears and shafts from damage.

MECHANICAL EARTH DRILLS



Little Beaver earth drills are incredibly fast. Operating at 360 RPM's, our augers rotate much faster than competitive units. Not only does this increase your drilling productivity, but it also results in cleaner holes.

The Little Beaver mechanical earth drill gets into areas inaccessible to skid-steer loaders. When traveling over manicured turf areas, the easy rolling wheeled carriage leaves no marks, eliminating costly turf restoration costs.

CHOOSE YOUR TIP

Standard augers are equipped with hard-faced, replaceable points and cutting blades. For added value, most blades are reversible.




Heavy-duty rock augers quickly cut through rocky soils. These augers operate most efficiently at slower RPM's and are recommended for 20:1 or 13:1 gear ratios.



When drilling hard clay, frozen ground, asphalt or hard pan soils, Little Beaver's carbide blades are the solution. The carbide blade replaces both the standard point and cutting blade.



A convenient snap button holds the auger securely to the transmission adaptor and lets you easily connect or remove augers and extensions without pins or tools.



Little Beaver offers a complete line of snap-on augers in both 36" and 42" lengths. Diameters range from 1.5" to 16". We also offer snap-on extensions, in both full flighted and tube configurations.





Carriage & Wheel Options

Customize your Little Beaver with a variety of engine, wheel and carriage options. Both the 5.5 hp and 8 hp models are available with Honda OHV or Briggs & Stratton engines.

10" pneumatic wheels are standard on 8 hp models, optional on 5.5 hp units. Engine protecting roll cages are optional on all models.

With its 20" semi-pneumatic wheels, the specially designed rick-sha carrier is ideal for navigating over the rough terrain often associated with geophysical job sites. A convenient pull handle and transmission cradle make it easy to smoothly move the earth drill to your exact drilling location.

	MDL-5B	MDL-5H	MDL-8B	MDL-8H
Engine brand/model	B&S Intek Pro OHV	Honda GX160 OHV	B&S Intek Pro OHV	Honda GX240 OHV
Engine horsepower	5.5 hp	5.5 hp	8.0 hp	8.0 hp
Oil alert system	Std.	Std.	Std.	Std.
Torque tube	Std.	Std.	Std.	Std.
Centrifugal clutch	Std.	Std.	Std.	Std.
7' flexible drive shaft	Std.	Std.	Std.	Std.
Snap-on auger adaptor	Std.	Std.	Std.	Std.
Gear reduction ratio*	10:1	10:1	10:1	10:1
RPM*	360	360	360	360
Wheel size**	8"	8"	10"	10"
Wheel type**	Semi-pneumatic	Semi-pneumatic	Pneumatic	Pneumatic
Shipping weight (dry)	125#	132#	147#	167#

SPECIFICATIONS

* Optional 13:1 or 20:1 gear reduction transmissions generate 277 or 180 RPM's, respectively

** Optional 10" pneumatic wheels are available for MDL-5B and MDL-5H



P.O. Box 840 • Livingston TX 77351

Toll Free: 800-227-7515 • Phone: 936-327-3121 • Fax: 936-327-4025

www.littlebeaver.com • email: sales@littlebeaver.com

Distributed by: