



Click Here To View
Item at

www.GapPower.com

*Sales • Rentals
Parts & Service*

Power Rake



MECHANICAL POWER RAKE

Our smooth, quiet power rake uses a centrifugal clutch to engage the blades so **dethatching is maintenance-free**. It also uses the same familiar controls as our other mechanical products. To save time, the blades can be changed without removing the reel — and blade height can be adjusted with a simple lever.

Optional accessories allow the power rake to be converted to a seeder for multi-purpose use.



MODEL	18" Mechanical Aerator	21" Single Hydraulic Aerator	30" Stand-On Aerator	MODEL	18" Mechanical Slit Seeder	20" Hydraulic Slit Seeder	MODEL	Mechanical Power Rake
Engine	Honda® GSV190 vertical shaft	Kawasaki® FJ180V	Kawasaki FS481V V-Twin	Engine	Honda GX160 horizontal shaft	Subaru® EX27	Engine	Honda GX160 horizontal shaft
Fuel Capacity	.290 gallon	1 gallon	5 gallons	Fuel Capacity	.82 gallon	1.6 gallons	Fuel Capacity	.82 gallon
Working Width	18"	21"	30"	Working Width	18"	20"	Working Width	18"
Depth	Up to 3"	Up to 3"	Up to 5"	Depth	1/4" – 1/2"	Up to 1"	Depth	1/8" – 1/4"
Width	29"	31.5"	48"	Width	28"	30"	Width	28"
Height	26" (handle folded) 43" (handle working)	38" (handle folded) 46" (handle working)	53"	Height	25" (handle folded) 37" (handle working)	28" (handle folded) 45" (handle working)	Height	25" (handle folded) 37" (handle working)
Length	38.5" (handle folded) 56.5" (handle working)	48" (handle folded) 50" (handle working)	65"	Length	38" (handle folded) 51" (handle working)	27" (handle folded) 52" (handle working)	Length	38" (handle folded) 51" (handle working)
Weight	263 lbs. (no weight) 278 lbs. (1 weight) 293 lbs. (2 weights)	285 lbs. (no weights) 320 lbs. (1 – 27 lb. weight)	1,015 lbs.	Weight	170 lbs.	260 lbs.	Weight	127 lbs.
Ground Speed	3.0 mph	4 mph fwd 2.2 mph rev	7.5 mph fwd 2.2 mph rev	Ground Speed	Push propelled	3 mph fwd 2.2 mph rev	Ground Speed	Push propelled
Coverage (Per Hour)	0.8 Acre	1.0 Acre	2.1 Acres	Seed Hopper Capacity	25 lbs.	40 lbs.	—	—
Tines	24	36	48	Blades	9 verticutting blades	10 verticutting blades	Blades	22 flail blades 1.5" spacing

All walk-behind machines comply with ANSI safety standards: B71.4 for commercial turf care equipment or B71.8 for OPE walk-behind ground-engaging equipment. Core and cutting depth vary depending on ground conditions.

Your local Toro dealer offers a complete selection of Toro equipment, as well as genuine Toro parts and service from knowledgeable technicians.

See your Toro dealer or Toro representative for details on the new turf renovation line, or visit toro.com today.



Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.