

ST PRO SERIES WEDGE CARGO



Standard Features

Height

- 6'6" Interior Height

Wedge Depth

- 18.5" Ext. Wedge Depth

Frame

- 6x2 Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- 24" On-Center Tube Roof Bows
- "WideTrac" Full-Width Interior Walls Without Fender Boxes (on 7' wides)

Hitch

- 7-Way Molded Plug
- 2-5/16" Coupler on 7K and 10K
- Adjustable 2-5/16" Coupler on 14K
- 4-Bolt Faceplate Pintle on 16K
- Safety Chains
- Zinc-Plated Setback Jack on 7K
- 7K Setback Jack on 10K & 14K
- HD 12K Setback Jack on 16K

Axle

- ***Torsion Axles**
- All Wheel Brakes

Wheels/Tires

- Easy Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)
- Radial Tires on Black Wheels (16K)

Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Luan Trim)
- 3/4" Engineered Wood Flooring Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/1 Wall Switch
- LED 6" Oval Tail Lights w/Rubber Mounted 3/4" Bullet Marker Lights (All Clear Lens)
- ***Integrated Backup Lights**

Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- Bright Nose Cap & Front Corners
- Bright Rear Hoop
- 24" Stoneguard w/Top Trim
- Seamless Aluminum Roof w/3" Top Trim
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

Door

- 32"x70" RV Side Door w/Aluminum Door Holder
- Heavy-Duty Rear Ramp Door w/Wood Flap or Rear Double Doors w/Aluminum Rear Door Holders
- Ramp Ratings - 7' wide = 2,250 lb.
8.5' wide = 4,100 lb.

Limited 3-Year Warranty

* Denotes New for 2020

SPECIFICATIONS

| | | 7' Wide (7K) | 7' Wide (10K) | 8.5' Wide (7K) | 8.5' Wide (10K) |
|---------------------------|-----|--|-----------------------|--|-----------------------|
| Model # | 12' | STW8412TA | STW8412TA-100 | - | - |
| | 14' | STW8414TA | STW8414TA-100 | - | - |
| | 16' | STW8416TA | STW8416TA-100 | STW10216TA | STW10216TA-100 |
| | 18' | STW8418TA | STW8418TA-100 | STW10218TA | STW10218TA-100 |
| | 20' | - | - | STW10220TA | STW10220TA-100 |
| | 24' | - | - | STW10224TA | STW10224TA-100 |
| GVWR (lb. / Axle) | | 7000 | 9900 | 7000 | 9900 |
| GAWR (lb. / Axle) | | 3500 | 5200 | 3500 | 5200 |
| Curb Weight | 12' | 1900 | 2150 | - | - |
| | 14' | 2040 | 2290 | - | - |
| | 16' | 2120 | 2400 | 2880 | 3350 |
| | 18' | 2220 | 2550 | 3260 | 3430 |
| | 20' | - | - | 3610 | 3760 |
| | 24' | - | - | 4170 | 4420 |
| Payload | 12' | 5100 | 7750 | - | - |
| | 14' | 4960 | 7610 | - | - |
| | 16' | 4880 | 7500 | 4120 | 6550 |
| | 18' | 4780 | 7350 | 3740 | 6470 |
| | 20' | - | - | 3390 | 6140 |
| | 24' | - | - | 2830 | 5480 |
| Frame | | 6x2 Tube | | 6x2, 1/8" Tube | |
| Cross Members | | C-Channel (16" On-Center) | | C-Channel (16" On-Center) | |
| Tongue | | 6x2 Tube | | 6x2, 1/8" Tube | |
| Wall Studs | | Tube (16" On-Center) | | Tube (16" On-Center) | |
| Roof Bows | | Tube (24" On-Center) | | Tube (24" On-Center) | |
| Coupler | | 2 5/16" Ball | | 2 5/16" Ball | |
| Jack | | 2K Setback | 7K Setback | 2K Setback | 7K Dropleg |
| Fenders | | Aluminum Teardrop | | Aluminum Teardrop | |
| Easy Lube Axles | | 22.5 Degree Up Torsion | | 22.5 Degree Up Torsion | |
| Tires | | 205/75R 15 LRC | 225/75R15 LRD | 205/75R 15 LRC | 225/75R15 LRD |
| Wheels | | 15", 5 on 4.5, Radial | 15", 6 on 5.5, Radial | 15", 5 on 4.5, Radial | 15", 6 on 5.5, Radial |
| Wheels | | Aluminum | | Aluminum | |
| Flooring | | Engineered Wood | | Engineered Wood | |
| Lights | | All LED Lights w/ Integrated Backup Lights | | All LED Lights w/ Integrated Backup Lights | |
| Electric Plug | | 7 Pole RV Molded Flat Blade | | 7 Pole RV Molded Flat Blade | |
| Exterior | | .030 Aluminum | | .030 Aluminum | |
| Overall Length | 12' | 198" | | - | |
| | 14' | 222" | | - | |
| | 16' | 246" | | 249" | |
| | 18' | 270" | | 273" | |
| | 20' | - | | 297" | |
| | 24' | - | | 345" | |
| Overall Width | | 102" | | 102" | |
| Overall Height | | 101" | | 101" | |
| Interior Height | | 78" | | 78" | |
| Interior Width | | 81" | | 97" (80.5" Between Fender Box) | |
| Interior Length | 12' | 153" | | - | |
| | 14' | 177" | | - | |
| | 16' | 201" | | 201" | |
| | 18' | 225" | | 225" | |
| | 20' | - | | 249" | |
| | 24' | - | | 297" | |
| Floor Height | | 18" | | 21" | |
| Rear Door Opening (WxH) | | 74" x 72.50" | | 90" x 72.50" | |
| Ramp Door Capacity (lbs.) | | 2250 | | 2250 | |

