



Quote Confidently
with

Malco's Power Assisted Cutter

Quickly and Safely Demo Standing-Seam Roofs!



FSXC

Length: 5.2" (132 mm)
Width: 7.55" (192 mm)
Height: 14.25" (362 mm)
Weight: 8.64 lbs. (4 kg)
DRILL NOT INCLUDED



FSXC2

Length: 5.65" (144 mm)
Width: 8.65" (220 mm)
Height: 14.85" (377 mm)
Weight: 12.15 lbs. (5.5 kg)

Malco's Power Assisted Cutter Features & Benefits

FSXC

- Quickly and effortlessly demo 1" or 1.5" single or double mechanical locks on stainless-steel, steel, copper, zinc, or aluminum standing seam roofing materials
- For use with a professional-grade cordless drill at a max speed of 56-feet/min (17 m/min)
- Designed to cut below the mechanical lock and through clips without damage to cutting discs
- Conveniently, safely and ergonomically demo roofs from a standing or kneeling position
- Arrives packaged in a premium IP 67 case with custom foam inserts
- Limited lifetime warranty

FSXC2

- Quickly and effortlessly demo 1.5" or 2" single or double mechanical locks on stainless-steel, steel, copper, zinc, or aluminum standing seam roofing materials
- For use with a professional-grade cordless drill at a max speed of 56-feet/min (17 m/min)
- Designed to cut below the mechanical lock and through clips without damage to cutting discs
- Conveniently, safely and ergonomically demo roofs from a standing or kneeling position
- Arrives packaged in a premium IP 67 case with custom foam inserts
- Limited lifetime warranty

Specifications

Standing Seam Metal Cutter

Catalog Number	Profile Description	Size in. (mm)	Steel Capacity	Aluminum Capacity (mm)	Copper Capacity (cm)	Stainless Steel	Zinc
FSXC	Standing Seam Cutter, 1"-1.5"	1"-1.5" Single & Double Lock (25 mm-38 mm)	24 ga.	.040" (1 mm)	20 oz. (591 cm)	26 ga.	.040" (1 mm)
FSXC2	Standing Seam Cutter, 2"	1.5"-2" Single & Double Lock (38 mm-50.8 mm)	22 ga.	.040" (1 mm)	20 oz. (591 cm)	26 ga.	.040" (1 mm)

Replacement Parts

Catalog Number	Description
FSXCRPC	Blades
FSXCRPC2	Blades



SEE IT IN ACTION!

