



Quote Confidently  
with

# Malco's Power Assisted Seamer

The world's **FASTEST** seamer on the market!



### FSXS

Length: 14.4" (366 mm)  
Width: 7.15" (182 mm)  
Height: 5.8" (147 mm)  
Weight: 12.5 lbs. (5.7 kg)  
*DRILL NOT INCLUDED*



### FSXS2

Length: 14.8" (376 mm)  
Width: 7.85" (200 mm)  
Height: 9.6" (244 mm)  
Weight: 15.4 lbs. (7 kg)

## Malco's Power Assisted Seamer Features & Benefits

### FSXS

- Quickly and effortlessly seam 1" or 1.5" single or double mechanical locks on stainless-steel, steel, copper, zinc, or aluminum standing seam roofing materials
- For use with a professional-grade cordless drill at a max speed of 98-feet/min (30 m/min)
- Eliminates the use of a hand seamer
- Conveniently, safely and ergonomically seam roofs
- Arrives packaged in a premium IP 67 case with custom foam inserts
- Limited lifetime warranty

### FSXS2

- Quickly and effortlessly seam 2" double mechanical locks on stainless-steel, steel, copper, zinc, or aluminum standing seam roofing materials
- For use with a professional-grade cordless drill at a max speed of 98-feet/min (30 m/min)
- Equipped with safety lanyard hook up point using 5/16-18 UNC thread
- Eliminates the use of a hand seamer
- Conveniently, safely and ergonomically seam roofs
- Arrives packaged in a premium IP 67 case with custom foam inserts
- Limited lifetime warranty

### Specifications

#### Standing Seam Seamer

Catalog Number	Description	Profile Size in. (mm)	Steel	Aluminum	Copper	Stainless	
			Capacity	Capacity (mm)	Capacity (cm)	Steel	Zinc
FSXS	Standing Seam Seamer, 1"-1.5"	1"-1.5" Single & Double Lock (25 mm-38 mm)	24 ga.	.040" (1 mm)	20 oz. (591 cm)	26 ga.	.040" (1 mm)
FSXS2	Standing Seam Seamer, 2"	2" Double Lock (50.8 mm)	22 ga.	.040" (1 mm)	20 oz. (591 cm)	26 ga.	.040" (1 mm)

### Replacement Parts

Catalog Number	Description
FSXSRPDW	Drive Wheels
FSXS2RPDW	Drive Wheels



**SEE IT IN ACTION!**

