



Click Here To View
Item at

www.GapPower.com

*Sales • Rentals
Parts & Service*

Skid Loader Trencher

SKIDTRE

Gap Power



625 Trencher



- ◇ For standard flow skid-steer loaders 14 to 22 gpm.
- ◇ 30" to 48" digging depth
- ◇ Various teeth assemblies available

- Standard Flow Chain Reduction for Skid Steers
- Boom lengths from 30" - 48"
- Chain widths from 6" - 12"
- Various chain type options
- Fully assembled

Boom Size	30"	36"	42"	48"
Trench Depth with Auger at 65° Digging Angle	30"	36"	42"	48"
Chain Widths	6"	6"	6"	6"
	8"	8"	8"	8"
	10"	10"	10"	NA
	12"	NA	NA	NA
Recommended Trenching Angle	65°	65°	65°	65°
Heightshaft Height	8"	8"	8"	8"
Length (overall)	66"	73"	79"	86"
Width (overall)	53"	53"	53"	53"
Height (overall)	32"	32"	32"	32"
Spoil Discharge Reach	18"	18"	18"	18"
Side Shift, Right of Center	17"	17"	17"	17"
GPM Requirements	14 to 22	14 to 22	14 to 22	14 to 22
Operating Pressure (PSI)	2000 to 3000	2000 to 3000	2000 to 3000	2000 to 3000