

Specifications	BB600X	BB720X	BB840X / BB840XQ	BB840X-P
Tractor Engine HP	30–120 hp		40–120 hp	
Hitch category / type	Cat 1 and 2 / clevis			pull-type
Cutting width	60"	72"	84"	84"
Transport width	67.5"	79.5"	91.5"	
Maximum overall length	104"	116"	128"	174"
Deck length	70"	84"	96"	
Cutting height range	2–12"			
Cutting capacity	3"			
Gearbox horsepower	120 hp			
Gearbox output shaft diameter	2"			
Blade tip speed	15,525 fmp	15,900 fmp	16,000 fmp / 16,300 fmp	16,000 fmp
Blade rotation	CCW			
Deck side depth	12.6"			
Approximate weight*	1,068 lbs	1,200 lbs	1,416 lbs	1,868 lbs
Blade dimensions	(2) .5" x 4"			
Blade composition	heat-treated alloy steel			
Blade carrier	round stump jumper			
Blade mount system	Quick Change pins			
Blade pin diameter	1.5"			
Cutting deck thickness	10 gauge			
Side frame thickness	.25"			
Tailwheel – laminated tire	5" x 16"			21" laminate 24" a/c 29" a/c
Dual tailwheel	single only	optional		standard with hydraulic height control
Safety-shielded driveline	Cat 4			
Driveline protection	slip-clutch			
Frame & deck support	3" x 4" full length structural beams			
Rear bumper	2" tubular			
Tractor PTO speed	540 rpm (BB840XQ 1000 rpm)			
Quick-hitch compatible	yes			n/a
Skid-shoes	heavy-duty replaceable			
Belting / Banding	chain shielding optional			
	Medium-duty			

* Weight without chain shielding.