



[PRODUCTS](#) > [EXTENSION LADDERS](#) > [D6200-2 SERIES](#) > 40FT TYPE IA FIBERGLASS D-RUNG EXTENSION LADDER D6240-2

40FT TYPE IA FIBERGLASS D-RUNG EXTENSION LADDER D6240-2

★★★★☆ 3.3 | 8 Reviews

5 out of 8 (63%) reviewers recommend this product

222 questions and 223 answers for this product

[Write a review](#)

[Ask a question](#)





VIDEOS



[BUY NOW](#)

Style: Multi-Section

Size: 40ft

Type: Type IA Duty Rating

[Resources](#) [Compatible Accessories](#)

The D6240-2 Fiberglass Two-Section 40ft Extension Ladder has non-conductive rails making this ladder ideal for working near electricity. With a duty rating of 300lb, the ladder is durable and long lasting. The exclusive Alflo® rung joint means Twist-Proof® performance on the job. The Traction-Tred® D rungs are slip-resistant and the side rails are interlocking. The dual action feet are for use on hard or penetrable surfaces and swivel easily. The base and fly sections separate easily to use the base section as a single ladder. The durable rail shield bracket and shoe help protect the bottom of the rail. The fly section rails are pre-pierced at the top for easy field installation of accessories.

FEATURES

- Exclusive Alflo® rung joint means Twist-Proof® performance
- 1.63in slip-resistant Traction-Tred® D-rungs
- Smooth operating pulley with polyester rope
- Interlocking side rails with internal rail guides on bottom of fly section securely connect rails
- Two sets of external guides at top of base section securely interlock rails
- Heavy duty extruded rung locks are spring loaded to operate smoothly
- Pre-pierced holes for easy field installation of accessories
- Base and fly separate easily to use base section as single ladder
- Combination rail shield bracket and shoe with SHU-LOK® and slip-resistant pad
- Molded rung braces on bottom step for increased durability
- Mar-resistant molded end caps

SPECIFICATIONS

DETAILS

Style	Multi-Section
Size	40ft
Type	Type IA Duty Rating
Load Capacity	300lb
Material	Fiberglass
Certifications	ANSI A14.5-2007, OSHA
Werner Benefit	Exclusive Alflo® rung joint means Twist-Proof® performance
Unique Features	Works Around Electricity
Color	Orange
	<input type="checkbox"/> Show Less

Foot Design	Shu-Lok ®, and spur plate
Max. Load	300lb
Number of Sections	2
Rung Type	D-Rung
Section x Rungs	2 x 20
UPC	051751030860

DIMENSIONS

Approx. Product Length (in)	240
Approx. Product Width (in)	19
Approx. Product Height (in)	6.31
Approx. Product Weight (lb)	88.5
Approx. Shipping Length (in)	240
Approx. Shipping Width (in)	19
Approx. Shipping Height (in)	6.9
Approx. Shipping Weight (lb)	88.5
Average Reach Height Extension Ladder (ft)	37ft 4in
Approx. Product Length (ft)	20
Approx. Closed Length (in)	240
Flange Dimension (in)	1.19in
Fly Width	16in
Max. Open Extended Height	35ft
Approx. Open Length (in)	420
Rails Dimension	3.31in
Rung Dimension	1.625in
Steps/Rung Dimension	1.625in

RESOURCES

[!\[\]\(74d4806277d7e73349d8e8c0897931e9_img.jpg\) View D6200-2 Series Page](#)