

Tufline®

SUBSOILERS

One & Two Shank Subsoiler Models

- Designed for 30 to 70 HP tractors
- 24", 28" and 32" x 1 1/4" Hi-strength shanks
- Single bar - 7" x 5" tube frame
- Heat treated points
- Parking stands standard
- Quick Hitch compatible



1S28

SINGLE BAR MODEL SERIES					
Model #	Cat.	Shanks	Frame	Spacing	Weight
1S24	Cat. 1	1-24"	26"	0	229#
1S28	Cat. 1	1-28"	26"	0	243#
1S242	Cat. 2	1-24"	49"	0	370#
1S282	Cat. 2	1-28"	49"	0	385#
2S24	Cat. 2	2-24"	49"	40"	520#
2S28	Cat. 2	2-28"	49"	40"	548#
2S2460	Cat. 2	2-24"	60"	52"	555#
2S2860	Cat. 2	2-28"	60"	52"	609#
2S2480	Cat. 2	2-24"	80"	72"	627#
2S2880	Cat. 2	2-28"	80"	72"	655#



2S28

Three Shank Subsoiler Models

- Designed for 75 to 130 HP tractors
- 24", 28" and 32" x 1 1/4" Hi-strength shanks
- Double bar - 7" x 5" & 5" x 3" tube frame
- Heat treated points
- Parking stands standard
- Quick Hitch compatible

DOUBLE BAR MODEL SERIES					
Model #	Cat.	Shanks	Frame	Spacing	Weight
3S2490	Cat. 2	3-24"	90"	Adj.	1160#
3S2890	Cat. 2	3-28"	90"	Adj.	1205#
3S3290	Cat. 2	3-32"	90"	Adj.	1264#
3S24107	Cat. 2	3-24"	107"	Adj.	1222#
3S28107	Cat. 2	3-28"	107"	Adj.	1267#
3S32107	Cat. 2	3-32"	107"	Adj.	1326#



3S2890

Well Built, Performance Driven Implements

To see our full line of Agricultural, Landscape, and Sportsman implements visit us on the web at

www.monroetufline.com

PO Box 7755, Columbus, MS 39705 Phone (662) 328-8347 Fax (662) 328-8361