

# PALLET FORKS

## RAIL PALLET FORKS

Adjustable ITA Class II forged tines.

**45.5"**  
FRAME WIDTH

UP TO  
**6200 LB**  
CAPACITY  
(VARIES BY MODEL)

**42" TO 60"**  
TINE LENGTHS

1. 3/4" BEVELED RAIL
2. BRICKGUARD FLUSH WITH TINES TO HELP STABILIZE LOADS
3. BRACING CENTERED ON QUICK TACH FOR EASY HOOKUP
4. BOLT-ON STEP INSTALLS ON EITHER SIDE

### RAIL PALLET FORK - HI-VIS



- REMOVE CENTER SECTION TO CHANGE TO A WALK-THROUGH BRICKGUARD
- 1/4" HIGH VISIBILITY BRICKGUARD

### RAIL PALLET FORK - WALK-THROUGH



- WALK-THROUGH DESIGN ALLOWS QUICK CAB ACCESS
- 1/4" HIGH VISIBILITY BRICKGUARD

### RAIL PALLET FORK - HEX-GUARD



- 3/16" CLASSIC VIRNIG BRICKGUARD

MODEL	4240	4840	4255	4855	6055	4862
Width: Overall w/Step / Frame (in.)				50.5 / 45.5		
Overall Height (in.)	37.0					
Tine: Length / Width / Thickness (in.)	42.0/4.0/1.375	48.0/4.0/1.375	42.0/4.0/1.5	48.0/4.0/1.5	60.0/4.0/1.5	48.0/4.0/1.75
Tine Space: Min / Max (in.)	8.8 / 40.9					
Approximate Weight (lbs)	370 <sup>1</sup>	390 <sup>1</sup>	390 <sup>1</sup>	405 <sup>1</sup>	440 <sup>1</sup>	420 <sup>1</sup>
Capacity (lbs)	4000	4000	5500	5500	5500	6200

<sup>1</sup>PF model weights listed. Subtract 15 lbs for PFWT model weights. Subtract 25 lbs for PFHG model weights.