



Click Here To View
Item at

www.GapPower.com

*Sales • Rentals
Parts & Service*

Makita Rotary Hammers

CORDLESS

CONCRETE

DRILLS

METALWORKING

SAWS

BENCHTOP

WOODWORKING

PNEUMATIC

POWER EQUIPMENT

2" Rotary Hammer

HR5000

Accepts Spline Bits, AC/DC



Air Cushion Design for Hard Hitting Action

- All ball-and-needle bearing construction for longer tool life
- Powerful 11 AMP motor for the most demanding applications
- Built-in clutch reduces gear damage by disengaging gears if bit binds
- 2-mode operation for "hammering only" or "hammering with rotation"
- Automatic brush cut-out system to protect motor

MODEL HR5000 INCLUDES: Hex wrench (#4; 783202-0, #5; 783203-8, #6; 783204-6), Tool case (150589-9)

Specifications:

Capacity: Concrete (w/core bits)	5-7/8"
No load speed	260 RPM
Blows per minute	2,100
Impact energy	11.8 J
AMPS (115V)	11.0
Bit type	Spline shank
Overall length	18-3/4"
Net weight	21.8 lbs.
Shipping weight	35.0 lbs.

1-9/16" Rotary Hammer

HR4041C

Accepts Spline Bits, Variable Speed



Powerful 12 AMP Motor; 230 - 460 RPM

- 2-mode operation for "hammering only" or "hammering with rotation"
- "No hammering while idling" helps increase tool life.
- Built-in clutch reduces gear damage by disengaging gears if bit binds
- Variable speed control dial enables user to match the speed to the application
- High quality aluminum housing for greater durability and tool life

MODEL HR4041C INCLUDES: Side handle (416549-4), Depth gauge (3212484), Tool case (1582578)

Specifications:

Capacities: Concrete	1-9/16"
Core Bit	4-5/8"
No load speed	230 - 460 RPM
Blows per minute	1,300-2,600
Impact energy	9.2 J
AMPS (115V)	12.0
Bit type	Spline shank
Overall Length	16-7/8"
Net weight	14.8 lbs.
Shipping weight	28.6 lbs.

1-1/4" AVT Rotary Hammer

HR3210C

NEW

Accepts SDS-PLUS Bits, Variable Speed



Anti-Vibration Technology for Operator Comfort

- Powerful 8.2 AMP motor; 1,650 - 3,300 BPM for demanding applications
- 3-mode operation for "rotation only", "hammering with rotation" or "hammering only" for multiple applications
- Variable speed control dial enables user to match the speed to the application
- One-touch sliding chuck for quick bit changes
- Built-in clutch reduces gear damage by disengaging gears if bit binds

MODEL HR3210C INCLUDES: Side handle (151769-0), Depth gauge (321248-4), Bit grease (194683-7), Tool case (824825-6)

Specifications:

Capacity: Concrete (w/core bits)	3-1/2"
No load speed	315 - 630 RPM
Blows per minute (BPM)	1,650 - 3,300
Impact energy	6.4J
AMPS (115V)	8.2
Bit type	Accepts SDS-PLUS
Overall length	15-5/8"
Net weight	11.4 lbs.
Shipping weight	28.0 lbs.

1-1/8" Rotary Hammer (Accepts SDS-PLUS Bits, Variable Speed, Rev.)

HR2811F



Light Up Your Drilling Surface with L.E.D. Power

- 3-mode operation for "rotation only", "hammering with rotation" or "hammering only" for multiple applications
- Extended service life of carbon brushes
- Recessed lock-on button for continuous use
- "No hammering when idling" helps increase tool life
- 0 - 1,100 RPM & 0 - 4,500 BPM for demanding applications

MODEL HR2811F INCLUDES: Side handle (154842-5), Depth gauge (324219-0), Tool case (824789-4)

Specifications:

Capacities: Concrete (w/core bits)	3-1/8"
Steel	1/2"
No load speed	0 - 1,100 RPM
Blows per minute	0 - 4,500
Impact energy	2.7 J
AMPS (115V)	6.7
Bit type	Accepts SDS-PLUS
Overall length	12-5/8"
Net weight	7.7 lbs.
Shipping weight	12.0 lbs.

VERSATILITY

3 modes: "Rotation Only", "Hammer with Rotation" and "Hammering Only"

1" Rotary Hammer

HR2432

Accepts SDS-PLUS Bits, Variable Speed, Rev.



Shown with optional bit

Built-in Dust Collection System

- 3-mode operation for "rotation only", "hammering with rotation" or "hammering only" for multiple applications
- Chisel rotates 360° with 40 different locking positions
- Powerful 6.7 AMP motor
- Variable speed; 0 - 1,000 RPM & 0 - 4,500 BPM
- One-touch sliding chuck for quick bit changes

MODEL HR2432 INCLUDES: Dust bag assembly (122708-7), Side Handle (152521-9), Bit grease (194683-7), Dust cap (421727-3), Tool case (824729-2)

Specifications:

Capacities: Concrete	1"
Steel	1/2"
No load speed	0 - 1,000 RPM
Blows per minute	0 - 4,500
Impact energy	2.2 J
AMPS (120V)	6.7
Bit type	Accepts SDS-PLUS
Overall length	16"
Net weight	6.9 lbs.
Shipping weight	16.5 lbs.

Rotary Hammers



1" Rotary Hammer (Accepts SDS-PLUS Bits, Variable Speed, Reversible)

NEW HR2475



Powerful 7.0 Motor

- 0 - 1,000 RPM & 0 - 4,500 BPM for demanding applications
- 3-mode operation for "rotation only", "hammering with rotation" or "hammering only" for multiple applications
- Ergonomic D-shaped handle with rubberized soft grip for increased comfort and control
- One-touch sliding chuck for quick bit changes
- Built-in clutch reduces gear damage by disengaging gears if bit binds

MODEL HR2475 INCLUDES: Side-handle (158057-6), Depth gauge (324219-0), Tool case (824695-3)

Specifications:

Capacities: Concrete	1"
Steel	1/2"
No load speed	0 - 1,100 RPM
Blows per minute	0 - 4,500
Impact energy	2.7 J
AMPS (115V)	7.0
Bit type	Accepts SDS-PLUS
Overall length	16-3/4"
Net weight	6.6 lbs.
Shipping weight	11.9 lbs.



15/16" Rotary Hammer

HR2470F Accepts SDS-PLUS Bits, Variable Speed, Reversible



Light Up Your Drilling Surface with L.E.D. Power

- 3-mode operation for "rotation only", "hammering with rotation", or "hammering only" for multiple applications
- Recessed lock-on button for continuous use
- "No hammering when idling" function helps increase tool life
- Compact design with padded grip and side handle for comfort
- Extended service life of carbon brushes
- One-touch sliding chuck for quick bit changes

MODEL HR2470F INCLUDES: Side-handle (158057-6), Depth gauge (324219-0), Tool case (824799-1)

Specifications:

Capacities: Concrete (w/core bits)	2-1/8"
Steel	1/2"
No load speed	0 - 1,100 RPM
Blows per minute	0 - 4,500
Impact energy	2.7 J
AMPS (115V)	6.7
Bit type	Accepts SDS-PLUS
Overall length	15-1/2"
Net weight	6.4 lbs.
Shipping weight	10.0 lbs.

11/16" Rotary Hammer

HR1830F Accepts SDS-PLUS Bits, Variable Speed, Reversible



Compact and Lightweight

- 2-mode operation for "rotation only" or "hammering with rotation"
- L.E.D. light illuminates the drilling surface
- Soft grip handle provides increased comfort on the job
- Extended service life of carbon brushes
- "No hammering when idling" function helps increase tool life
- Built-in clutch reduces gear damage by disengaging gears if bit binds

MODEL HR1830F INCLUDES: Side-handle (154842-5), Depth gauge (415486-9), Tool case (824650-5)

Specifications:

Capacities: Concrete	11/16"
Steel	1/2"
No load speed	0 - 1,500 RPM
Blows per minute	0 - 5,000
Impact energy	1.2 J
AMPS (115V)	4.2
Bit type	Accepts SDS-PLUS
Overall length	10-7/8"
Net weight	4.2 lbs.
Shipping weight	11.0 lbs.

36V 1" LXT Rotary Hammer

BHR261 Accepts SDS-PLUS Bits, Variable Speed, Rev., w/Light



Corded Speed & Power Without the Cord

- Makita-built motor delivers 0 - 1,200 RPM & 0 - 4,800 BPM
- Ergonomically designed vibration absorbing handle
- 3-mode operation for "rotation only", "hammering with rotation" or "hammering only" for multiple applications
- One-touch sliding chuck for quick bit changes
- Built-in clutch reduces gear damage by disengaging gears if bit binds

MODEL BHR261 INCLUDES: 2 ea. Battery BL3626, Rapid Optimum Charger (DC36RA), Side handle (450990-1), Depth gauge (324219-D), Tool case (824874-3)

Specifications:

Capacities: Concrete (1")	Steel (1/2")
No load speed	0 - 1,200 RPM
Blows per minute	0 - 4,800 BPM
Impact energy	3.0 J
Bit type	Accepts SDS-PLUS
Battery	36V LXT Lithium-Ion
Overall length	14-1/4"
Net weight	9.9 lbs. (w/battery)
Shipping weight	25.3 lbs.

18V LXT 7/8" Rotary Hammer

BHR241 Accepts SDS-PLUS Bits, Variable Speed, Rev.



Faster Drilling with Synchronized RPM & BPM

- Makita-built variable speed motor delivers 0 - 1,100 RPM & 0 - 4,000 BPM
- 3-mode operation for "rotation only", "hammering with rotation" or "hammering only" for multiple applications
- Large 2-finger variable speed trigger for added convenience
- One-touch sliding chuck for quick bit changes

MODEL BHR241 INCLUDES: 2 ea. Battery BL1830, Rapid Optimum Charger (DC18RA), Side handle (158057-6), Depth gauge (324219-0), Contractor bag (821016-X)

MODEL BHR241Z: Tool Only - Battery, charger and bag not included

Specifications:

Capacities: Concrete (7/8")	Steel (1/2")
No load speed	0 - 1,100 RPM
Blows per minute	0 - 4,000 BPM
Impact energy	1.9 J
Bit type	Accepts SDS-PLUS
Battery	18V LXT Lithium-Ion
Overall length	16-3/8"
Net weight	7.7 lbs. (w/battery)
Shipping weight	16.8 lbs.

CORDLESS
CONCRETE
DRILLS
METALWORKING
SAWS
BENCHTOP
WOODWORKING
PNEUMATIC
POWER EQUIPMENT