



[Click Here To View](#)
[Item at](#)

www.GapPower.com

*Sales • Rentals
Parts & Service*

Honda Pumps



HONDA



The WH series pumps offer high-pressure output, so they're perfect for high-pressure applications like using sprinklers or nozzles. High-pressure pumps are compact, easy to start, extremely reliable and feature a powerful Honda four-stroke commercial-grade overhead valve engine offering superior torque and fuel efficiency.




Thanks to the use of Honda four-stroke engines and superior technology, Honda water pumps offer smooth, quiet operation.

WH15XK1C1



- High-pressure (55 psi max.), centrifugal, self-priming 1.5" pump
- 115 gal/min capacity
- Easy-starting Honda OHV commercial-grade engine
- Lightweight aluminum case
- Cast iron impeller & volute

- Easy-carry handle




WH20XK1AC1



- High-pressure (61 psi max.), centrifugal, self-priming 2" pump
- 134 gal/min capacity
- Easy-starting Honda OHV commercial-grade engine
- Lightweight aluminum case
- Cast iron impeller & volute

- Easy-carry handle



WATER PUMP SPECIFICATIONS

De-Watering		
H I G H - P R E S S U R E		
Model	WH15XK1	WH20XK1A
Honda 4-stroke, single cylinder, air cooled engine	GX120 OHV	GX160 OHV
Displacement	118cc	163cc
Compression ratio	8.5:1	8.5:1
Honda Oil Alert*	NN/A	N/A
Pump type	High Pressure Centrifugal Self-priming	High Pressure Centrifugal Self-priming
Volute	Rigid Mounted Cast Iron	Rigid Mounted Cast Iron
Impeller	Cast Iron	Cast Iron
Mechanical Seal (Pump case/impeller)	Carbon/Ceramic	Carbon/Ceramic
Priming time	40 sec. at 16.4 ft.	60 sec. at 16.4 ft.
Drive system	Direct	Direct
Discharge capacity	115 gal/min	134 gal/min
Suction port diameter	1.5" NPT	2" NPT
Discharge port diameter	1.5" NPT	2" NPT
Total head lift	127 ft.	141 ft.
Suction head lift	26 ft.	26 ft.
Maximum pressure	55 psi	61 psi
Solids handling	N/A	N/A
Dimensions (LxWxH)	16.3" x 14.2" x 15.9"	16.7" x 14.8" x 15.9"
Dry weight	48.5 lbs.	51.8 lbs.
3-Year Limited Residential and Commercial Warranty	•	•