



PREMIER™ DUCTABLE UNIT HEATERS



Premier 170 DF

Btu/h Rating				
Maximum			170,000	
Intermediate			-	
Ignition System			Direct Spark	
Heated Air Output (CFM)			1,200	
Dual Fuel Capability			Yes	
Fuel Consumption (max.)				
Liquid Propane Gas (lbs./hr.)			7.9	
Natural Gas (cu.ft/hr.)			170.0	
Inlet Gas Pressure				
Propane min./max. (in W.C.)			11.0/13.5	
Natural Gas min./max. (in. W.C.)			11.0/13.5	
Two Stage Output			No	
Electrical Supply (Volts/Hz/Phase)			115/60/1	
Amps (Starting /Cont. Oper.)			7.3/5.0	
Amps (15 amp circuit)			Yes	
Motor Horsepower			1/3	
Cabinet Material			Exclusive Tri-shield Coating**	
Wheels			Semi-pneumatic	
Fan Only Mode			S	
Dimensions (in.)				
Length			32.3	
Width			24.3	
Height			32.0	
Net Weight (lbs.)			154.0	
Shipping Weight (lbs.)			162.0	
Gas Pressure Regulator (with POL)			S	
Thermostat (Weatherproof with 20' cord)			S	
Gas Hose			15'	
Ducting*** (12" or 18" dia. x 12' length)			Gray-26346 Light Duty-26348	
CSA U.S. / Canada Certification			Yes	

\*Amps spike over 15 during initial start-up. Check breaker capability

\*\* Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

\*\*\*Gray, White, and Light Duty ducts are Optional. Premier 80 and 170 require the 12" diameter duct, and the Premier 350 requires the 18" diameter duct. Part numbers listed. Duct part numbers differ on previously built models. Please call L.B. White for specific part numbers.

S=Standard O= Optional



World Provider of Innovative Heating Solutions