

# The Metro<sup>®</sup>

Automatic Feed

*A tough machine in a compact lightweight package.*

The variable speed power cable feed makes the Metro easier for your customers to use. The automatic feed drives cable into the line at up to 20 feet per minute. Put the feed in reverse and it retracts the cable easily too. The power cable feed and guide tube combination allows the cable to feed smoothly into the line while keeping your customers hands clean and away from the spinning cable.

The Metro's heavy-duty reinforced frame takes rough handling in the field. The big 10" heavy duty wheels and a truck loading wheel make it easier to transport the machine to and from the job. A cutter holder on the frame keeps all the cutters within easy reach. And the fold down handle makes the machine more compact to take up less space in the truck. With tough 9/16" Flexicore<sup>®</sup> cable, The Metro clears 3", and most 4" lines up to 75 feet long.



#### Folding Handle

Handle folds to take less space in car trunk.

#### Specifications:

##### Weight:

92 lbs. (42 kg) without cable.

##### Dimensions:

27" deep x 18-1/2" wide x 46" high. (26" high with handle folded down)  
68.5 cm deep x 47 cm wide x 117 cm high. (66 cm with handle folded down)

##### Cage Capacity:

50 ft. x 9/16" (15 m x 14.3 mm).  
75 ft. x 9/16" (22.5 m x 14.3 mm). 100 ft. x 1/2" (30 m x 12.7 mm).

##### Drum Removal:

Remove one bolt and slide drum off shaft.

##### Motor:

1/3 hp with capacitor start, forward-off-reverse switch, 20 ft. power cord and ground fault circuit interrupter.

##### Foot Switch:

Pneumatic, with no electrical contact between pedal and motor.

##### Safety Slip Clutch:

Protects cable and operator.

**Wheels:** 10" semi-pneumatic with roller bearings.

##### Power Cable Feed:

Drives and retracts cable at variable speed without having to reverse motor rotation.

##### Wheel brake:

Passive wheel brake system holds the machine in place on the job and in the truck.

**Truck Loading Wheel:** Enables one person to lift machine into truck bed.

##### Cutter Holder:

Cutter Holder on the frame keeps all the cutters within easy reach.

##### Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

**Cables:** Left-wound Flexicore wire rope center. 9/16" diameter for 3" to 4" lines (Not for roots).

**Cutter Set:** Arrow Head, 1-1/2" U-Cutter, 2" U-Cutter, and Small Retrieving Tool. See Cutters & Cables.

Instructional Video included.



**General** General Wire Spring Co.  
**PIPE CLEANERS**  
McKees Rocks, PA 15136 USA  
800-245-6200 or 412-771-6300

www.drainbrain.com

**The toughest tools down the line.™**