



Click Here To View
Item at


www.GapPower.com

*Sales • Rentals
Parts & Service*

RTV-X Series

Specifications

RTV-X900



| Model | | | RTV-X900 Worksite | |
|--|----------------------------|-------------|---|------------------|
| Body color | | | Kubota Orange | |
| Engine | Make | | KUBOTA D902-E4-UV | |
| | Type | | 3-cylinders, 4-cycle, diesel, OHV | |
| | Displacement | cu.in (cc) | 54.8 (898) | |
| | Horsepower | HP (kW)/rpm | 21.6 (16.1) @3200 | |
| | Cooling system | | Liquid | |
| | Battery | | 540 CCA | |
| Transmission | | | Variable hydro transmission (VHT-X) | |
| Gear selection | | | Hi-Lo range forward, neutral, reverse | |
| Max. traveling speed | | | mph (km/h) | |
| 4WD system | | | mph (km/h) | |
| 4WD system | Front differential | | Limited-slip differential | |
| | Rear differential | | Foot operated differential lock | |
| Steering | | | Hydrostatic power | |
| Brakes | Front / Rear | | Wet-disc brakes | |
| | Parking brake | | Rear wheel, hand operated | |
| Suspension | Front suspension | | Independent, Dual A-arms with adjustable spring preload | |
| | Front suspension travel | in. (mm) | 8 (205) | |
| | Rear suspension | | Independent with coil over shock | |
| | Rear suspension travel | in. (mm) | 8 (205) | |
| Headlights | | | Two 37.5 watt halogen | |
| Occupant Protective System (OPS) | Tubular overhead structure | | 2.0 (50.8) steel tube | |
| | Seat belts | | 2-point | |
| | Certification | | SAE J2194 and OSHA 1928 ROPS | |
| Dimensions | Length | in. (mm) | 122.5 (3110) | |
| | Width | in. (mm) | 63.2 (1605) | |
| | Height, overall | in. (mm) | 79.5 (2020) | |
| | Front tread centers | in. (mm) | 48.8 (1240) | |
| | Rear tread centers | in. (mm) | 48.8 (1240) | |
| | Wheelbase | in. (mm) | 80.5 (2045) | |
| | Turning radius | ft. (m) | 13.1 (4.0) | |
| Weight | | | lbs. (kg) | |
| Towing capacity | | | lbs. (kg) | |
| Payload capacity | | | lbs. (kg) | |
| Ground clearance | Front | in. (mm) | 10.5 (266) | |
| | Rear | in. (mm) | 10.4 (263) | |
| | Under foot platform | in. (mm) | 11.0 (280) | |
| Cargo bed | Material | | Steel | |
| | Width x Length x Depth | in. (mm) | 57.7 (1465) x 40.5 (1030) x 11.2 (285) | |
| | Volume | cu ft. (m3) | 15.2 (0.43) | |
| | Bed height (unloaded) | in. (mm) | 34.9 (887) | |
| | Cargo bed load | lbs. (kg) | 1102 (500) | |
| | Dump | | | Hydro power lift |
| Fuel tank capacity | U.S. gals (L) | | 7.9 (30) | |
| Sound rating at operator's ear | dB. (A) | | 85 | |
| Tires | Front and Rear | ATV | 25x10-12, 6PLY | |
| | | HDWS | 25x10-12, 6PLY | |
| | | TURF | 25x10-12, 4PLY | |
| Front guard design | | | Center and bumper | |
| Alloy wheel (not available with Turf tire) | | | Opt. | |
| Hydraulic bed lift | | | Std. | |
| Spray-on Bed Liner | | | Opt. | |

*New SAE J1940

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.