

V20 MINI SKID STEER POWER RAKE

Available widths 48", 60"

Grade soil and gravel, prepare seedbeds, and remove debris.

CHOOSE MINI SKID MOUNT:

- TORO®/MINI UNIVERSAL
- BOBCAT®
- ASV®
- Universal skid steer quick tach mount not available.




Shown with optional Hydraulic Angle



Standard with manual angle.

10-18 GPM RECOMMENDED FLOW RATE	DIRECT DRIVE MOTOR	MANUAL & HYDRAULIC ANGLE AVAILABLE	GREATER THAN 515 LB LOADER OPERATING CAPACITY
----------------------------------------------	------------------------------	------------------------------------------------------	-------------------------------------------------------------

1. BI-DIRECTIONAL OPERATION IN FORWARD OR REVERSE
2. REVERSIBLE & REMOVABLE END PLATES
3. ANGLE THE RAKE 25° LEFT OR RIGHT
4. GUARDED MOTOR
5. FLOATING DESIGN FOR A SMOOTH FINISH & PROVIDES FULL DOWN PRESSURE CAPABILITY
6. CARBIDE TIP TEETH
7. FLAT-FREE URETHANE FILLED TIRES FOR EASY MAINTENANCE



**OPTION:
HYDRAULIC
ANGLE**
Angle the rake from the loader.

	MODEL	CPR48	CPR60
	Raking Width (in.)	48.0	60.0
	Raking Width at Full Angle (in.)	44.0	54.2
	Overall Width (in.)	56.0	68.0
	Overall Height (in.)		22.2
	Overall Depth (in.)		52.6
	Drum Diameter (in.)		7.0
	Number of Teeth	62	78
	Float Link Angle (degrees)		22
	Max Rake Angle (degrees)		25
	Recommended Flow Rate (GPM)	10-18 Standard Flow Only	
	Approximate Weight (lbs)	520*	565*
	Recommended Loader Capacity	Greater than 515 lbs	

*ASV® mount adds approximately 30 lbs and Bobcat® mount adds 25 lbs to model weight.