



Click Here To View
Item at

www.GapPower.com

*Sales • Rentals
Parts & Service*

CYCLONE



Exceptional Performance

Intec's highly portable Cyclone processes over 800 pounds of cellulose or 200 pounds of fiberglass per hour while weighing only 142 pounds with our recently enhanced aluminum airlock. This system provides ease of transportation to the job site, in addition to timely installation of attic insulation – less than 1 hour to install R-19 cellulose and under 1-1/2 hours to install R-19 fiberglass in a 1000 square foot attic.

Ease of Use

The system's control panel and wired remote provide for ease of operation from either the unit or the attic. Ease of transfer between retail location and jobsite is enabled by its small size & built-in wheels. Hose, connectors and clamps come standard -- everything you need to begin using immediately.



Capabilities

The Cyclone comes equipped with a slide gate to control material flow -- providing its users sidewall retrofit capabilities in addition to attic installations. Be it cellulose drill & fill, or fiberglass dense pack, this system can do-it-all.



Total Reliability

The powder coated exterior enables demanding use, while the automatic chain tensioner provides for high uptime capability. Minimal maintenance, combined by support from Intec's technical service team, provides for a system experience offering some of the highest industry uptimes and lowest life-cycle costs.

When looking for a capable, versatile, Do-It-Yourself unit with a track record of rigorous use, look no further than Intec's Cyclone.

COMES STANDARD WITH

PRODUCTION



- (2) 50' x 2.5" Blowing hose
- (1) 2.5" Steel hose connector
- (3) 2.5" Stainless steel hose clamps
- (1) 100' Remote cord
- (1) Slide gate



Cellulose Production
800 lbs per hour



Fiberglass Production
204 lbs per hour


Specifications



Dimensions	38"H x 29"W x 29" L
Weight	142 lbs
Weight (shipping)	215 lbs
Production (Single Blower)	800 lbs/hr- Cellulose 204 lbs/hr- Fiberglass
Hose Outlet Size	2.5"
Remote Cord	16/4 x 100'
Hopper Capacity	5.2 cu. ft.
Drive motor	115VAC 1/2 HP - 7.8 amps 230VAC 1/2 HP - 4.1 amps
Airlock	6" Aluminum
Blower	115VAC 1 or 2, 2 stage, 8 amp, 104 cfm 230VAC 1 or 2, 2 stage, 4 amp, 126 cfm
Electrical*	115 VAC / 60 Hz
Power cord	(1) 14/3 x 6'
Warranty	1 year limited; 90 days electric, airlock system and blower

* 230 VAC / 50 Hz available upon request

Electrical Features



- Agitator Switch
- Blower Switch
- Agitator Circuit Breaker
- Remote Cord
- Power Cord

Options

Hopper Extension



Applications

- Attics
- Dense Pack
- Drill & Fill

Accessories



Pressure Gauge



Hose Bag



150'
Remote Cord



Hose Swivels
2-6" Available

Distributed By

The Intec Pledge

Provide the finest equipment in the industry with the highest standards while continuing to strive for 100% satisfaction.

Manufactured By



1-800-666-1611

3771 Monarch Street
Erie, CO 80516 USA
Local: 303-833-6644
Fax: 303-833-6650

www.inteccorp.com