



Click Here To View
Item at

www.GapPower.com

*Sales • Rentals
Parts & Service*

Honda Pumps



HONDA

De-Watering Pumps

Honda de-watering pumps are designed for applications including irrigation, flood control, light construction, and swimming pool draining. Choose from an extensive selection of models with different features, pumping capacity and technical characteristics. With all these choices, there's no doubt you'll find one that fits your needs perfectly. Plus, every one of these pumps is compact, lightweight, and features something that professionals worldwide already count on – legendary Honda performance.




Honda's WX series pumps are an excellent choice for homeowners, gardeners and boat owners. Powered by Honda's easy-starting, quiet-running mini four-stroke engine, these models deliver exceptional performance in a truly lightweight package.




WX10K1A

- Lightweight aluminum pump – weighs only 13.4 lbs.
- 37 gal/min capacity
- Includes garden hose adaptor, 16.5' suction hose, clamps and strainer
- Powerful, easy-starting, Honda mini four-stroke engine
- Uses regular gasoline – no mixing of oil and gas



WX15AX2

- Lightweight aluminum pump – weighs only 20 lbs.
- 72 gal/min capacity
- Powerful, easy-starting, Honda mini four-stroke engine
- Protected by Honda Oil Alert®
- Hose clamps and strainer included



WATER PUMP SPECIFICATIONS

De-Watering					
		LIGHTWEIGHT		GENERAL PURPOSE	
Model	WX10K1A	WX15AX2	WB20XK2	WB30XK2	
Honda 4-stroke, single cylinder, air cooled engine	GX25 OHV	GXH50 OHV	GX120 OHV	GX160 OHV	
Displacement	25cc	49cc	118cc	163c	
Compression ratio	8.0:1	8.0:1	8.5:1	8.5:1	
Honda Oil Alert®	N/A	Std	Std	Std	
Pump type	Lightweight Centrifugal Self-priming	Lightweight Centrifugal Self-priming	General Purpose Centrifugal Self-priming	General Purpos Centrifugal Self-priming	
Volute	Aluminum	Aluminum	Rigid Mounted Cast Iron	Rigid Mounted Cast Iron	
Impeller	Aluminum	Aluminum	Cast Iron	Cast Iron	
Mechanical Seal (Pump case/impeller)	Carbon/Ceramic	Carbon/Ceramic	Silicone Carbide/Silicone Carbide	Silicone Carbide/Silicone Carbide	
Priming time	80 sec. at 16.4 ft.	120 sec. at 16.4 ft.	110 sec. at 16.4 ft.	150 sec. at 16.4 ft.	
Drive system	Direct	Direct	Direct	Direct	
Discharge capacity	37 gal/min	72 gal/min	152 gal/min	275 gal/min	
Suction port diameter	1.0" NPT	1.5" NPT	2" NPT	3" NPT	
Discharge port diameter	1.0" NPT	1.5" NPT	2" NPT	3" NPT	
Total head lift	118 ft.	125 ft.	92 ft.	85 ft.	
Suction head lift	26 ft.	26 ft.	26 ft.	26 ft.	
Maximum pressure	51 psi	54 psi	40 psi	37 psi	
Solids handling	N/A	N/A	5/16"	5/16"	
Dimensions (LxWxH)	12.8" x 8.7" x 11.8"	12.8" x 10.8" x 14.8"	17.9" x 14.4" x 16.5"	20.1" x 15.2" x 17.9"	
Dry weight	13.4 lbs.	19.8 lbs.	46 lbs.	60 lbs.	
3-Year Limited Residential and Commercial Warranty			●	●	
Construction					
		TRASH		DIAPHRAGM	
Model	WT20XK3A	WT30XK3A	WT40XK2A	WDP30XK1AT	
Honda 4-stroke, single cylinder, air cooled engine	GX160 OHV	GX240 OHV	GX340 OHV	GX120 OHV	
Displacement	163cc	242cc	337cc	118cc	
Compression Ratio	8.5:1	8.2:1	8.0:1	8.5:1	
Honda Oil Alert®	STD	STD	STD	STD	
Pump type	Trash Centrifugal Self-priming	Trash Centrifugal Self-priming	Trash Centrifugal Self-priming	Diaphragm Self-priming	
Volute	Rigid Mounted Cast Iron w/ Stainless Wear Plate	Rigid Mounted Cast Iron w/ Stainless Wear Plate	Rigid Mounted Cast Iron w/ Stainless Wear Plate	N/A	
Impeller	Conical Cast Iron	Conical Cast Iron	Conical Cast Iron	N/A	
Mechanical seal (Pump case/impeller)	Silicone Carbide/Silicone Carbide	Silicone Carbide/Silicone Carbide	Silicone Carbide/Silicone Carbide	N/A	
Priming time	70 sec. at 16.4 ft.	100 sec. at 16.4 ft.	160 sec. at 16.4 ft.	20 sec. at 20.0 ft.	
Drive system	Direct	Direct	Direct	Direct	
Discharge capacity	187 gal/min	319 gal/min	433 gal/min	80 gal/min	
Suction port diameter	2" NPT	3" NPT	4" NPT	3" NPT	
Discharge port diameter	2" NPT	3" NPT	4" NPT	3" NPT	
Total head lift	98 ft.	89 ft.	85 ft.	50 ft.	
Suction head lift	26 ft.	26 ft.	26 ft.	24 ft.**	
Maximum pressure	42 psi	39 psi	37 psi	N/A	
Solids handling	13/16 inches	1 1/16 inches	1 1/16 inches	2.4"	
Dimensions (LxWxH)	24.4" x 18.1" x 18.3"	26.0" x 19.5" x 20.3"	28.9" x 21.1" x 22.2"	31.5" x 30.5" x 25.7"*	
Dry weight	104 lbs.	132 lbs.	172 lbs.	163 lbs.	
3-Year Limited Residential and Commercial Warranty	●	●	●	●	

* With handlebar over engine ** 16 ft dry, 24 ft primed