

# MINI SKID STEER

## V20 MINI SKID SNOW / LIGHT MATERIAL BUCKET

Available widths  
36", 42", 48", 54" & 60"

High volume design for hauling snow, mulch, and light materials.



AVAILABLE  
EDGE OPTION:  
STANDARD  
BOLT-ON

34.7" DEPTH	23.3" HEIGHT	< 1650 LB LOADER OPERATING CAP.
----------------	-----------------	---------------------------------------

1. 3/16" SHELL & SIDE PLATES
2. 1/2" x 4" WELD-ON EDGE
3. WINDOWS FOR BETTER VISIBILITY. AVAILABLE WITH A SOLID BACK
4. UP TO 14 CU FT STRUCK CAPACITY (VARIES BY MODEL)
5. UP TO 17 CU FT HEAPED CAPACITY (VARIES BY MODEL)

### CHOOSE FROM THREE MINI SKID MOUNTS:

- MINI UNIVERSAL (All brands except Bobcat® and ASV®)
- BOBCAT® Mini
- ASV® Mini

NOTE: None of the above are compatible with universal skid steer mount.

	MODEL CLMB36	CLMB42	CLMB48	CLMB54	CLMB60
Width: Overall / Inside (in.)	36.0 / 34.6	42.0 / 40.6	48.0 / 46.6	54.0 / 52.6	60.0 / 58.6
Overall Height (in.)	23.3				
Depth: Overall / Inside (in.)	34.7 / 31.3				
Capacity: Struck / Heaped (cu. ft.)	8.3 / 9.9	9.8 / 11.7	11.3 / 13.5	12.8 / 15.3	14.3 / 17.1
Bucket Back Angle (degrees)	70				
Shell Thickness (in.)	0.19				
Side Plate Thickness (in.)	0.19				
Approximate Weight (lbs)	215 <sup>1</sup>	235 <sup>1</sup>	255 <sup>1,2</sup>	275 <sup>1,2</sup>	295 <sup>1,2</sup>
Recommended Loader Capacity	Less than 1650 lbs				

<sup>1</sup>Bobcat® mount adds 10 lbs to model weight, and <sup>2</sup>ASV® mount adds approximately 5 lbs.

## V20 MINI SKID STEER SKELETON ROCK BUCKET

Available widths 36", 42" & 48"

Pick up rocks and leave dirt behind.



0.25" GRADE 50 STEEL TINES	2.9" TINE SPACING	31.2" DEPTH	20.4" HEIGHT	> 500 LB LOADER OPERATING CAP.
-------------------------------	-------------------------	----------------	-----------------	--------------------------------------

1. EVERY TINE IS MADE FROM ONE PIECE OF STEEL FOR MAXIMUM RIGIDITY
2. NOTCH NEAR TINE TIPS HOLDS ROCKS SECURELY
3. TINE TIPS FULLY GUSSETED FOR ADDED STRENGTH

### CHOOSE FROM THREE MINI SKID MOUNTS:

- MINI UNIVERSAL (All brands except Bobcat® and ASV®)
- BOBCAT® Mini
- ASV® Mini

NOTE: None of the above are compatible with universal skid steer mount.

	MODEL CSR36	CSR42	CSR48
Width: Overall / Inside (in.)	36.0 / 35.0	40.9 / 39.9	46.8 / 45.8
Overall Height (in.)	20.4		
Depth: Overall / Inside (in.)	31.2 / 20.5		
Number of Tines (w/ sides)	13	15	17
Space Between Tines (in.)	2.9		
Tine Thickness (in.)	0.25 <sup>1</sup>		
Side Plate Thickness (in.)	0.25 <sup>1</sup>		
Approximate Weight (lbs)	180 <sup>2</sup>	205 <sup>2</sup>	225 <sup>2,3</sup>
Recommended Loader Capacity	Greater than 500 lbs		

<sup>1</sup>Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).

<sup>2</sup>Bobcat® mount adds 15 lbs to model weight, and ASV® mount adds approximately 30 lbs.