

S36 HEPA Dust Extractor

Creating Clean Air for Construction, Abatement, and Restoration



Introducing the most powerful single-phase HEPA Dust Extractor on the market today. Three large, commercial-grade vacuum motors provide over 353CFM and 110 inches of waterlift, plenty of power to handle any mid-size planetary floor grinder.

Like all Ermator Dust Extractors, the model S36 is equipped with Jet Pulse filter cleaning, "drop-down" dust collection in a plastic bag and tested and certified HEPA filtration. What makes the S36 truly unique and unmatched in the concrete grinding and polishing industry is the quantity and size of its filters. **It has a massive pre-filter with over 50-square feet of media, constructed in a cone-shape to reduce filter loading.** The unique shape of the S36 pre-filter also improves filter cleaning, when necessary, via the Jet Pulse filter cleaning system. Our competitors have difficulty including a single HEPA filter with their vacuums. The S36 is equipped with 3 independently tested and certified HEPA filters to guarantee that the vacuum exhaust is absolutely dust-free!

The S36 is also unmatched in its portability. Its surprisingly innovative dolly design makes loading and unloading a breeze. Once on the jobsite, this dust extractor easily navigates congested floor areas via a steel frame mounted on large rear wheels and lockable front swivel casters.



- Jet Pulse: for efficient filter cleaning
 - Strong, ergonomic handles: also good for truck loading Large ergonomic handles for easy tilt, transfer and loading, especially up and down steps.
 - 2.0" inch hose inlet: with tight air seal
 - Three tested and certified HEPA filters: each mounted above a single vacuum motor.
 - Longopac® Dustless: drop-down disposal via Longopac bag system.
 - 10-inch Rear Wheels: non marking
 - Front Swivel Casters: 4-inch, lockable
- Comes with 2" and 2.5" hoses and tools

The S36 Features Longopac®


A drop-down dustless disposal system



Pull the bag down.



Attach two ties with a 5" gap



Cut between the ties.



Manometer: measures the negative pressure within the tank and alerts the operator when the filters need servicing.



Central Exhaust: concentrated air exhaust may be vented away from jobsite with duct hose.



S36 Specifications

CFM:	353
HP:	5.1
AMP:	18
Volt:	110
Water lift:	110
Weight:	134
Product Code:	200900057