



[Click Here To View](#)
[Item at](#)

www.GapPower.com

Sales • Rentals
Parts & Service

1½" Standard Pressure Pneumatic Concrete and Steel Pinner



SCP40XP

Does not require costly proprietary high pressure compressor system - works with conventional air compressors, hoses and fittings.

Applications

Designed for fastening of drywall track, wood furring, hat channel, ceiling grid to concrete, concrete block and steel, wire lath to block/concrete*.

Features


- 10 Times faster than powder-actuated systems
- No Licensing required to operate
- Operates in Contact or Sequential Trigger actuation modes
- Works with conventional air compressors, hoses, and fittings
- Operates in extreme temperature and altitudes

Specifications

Item #: 7J0001N Contact or Sequential actuation triggers
Reg. Operating Pressure: 80-120 psi (5.5-8.3 bar)
Air Consumption (60 cycles per min.): 5.2 scfm
Air Inlet: 1/4" NPT
Tool Weight: 7.1 lbs (3.2 kg)
Height: 12.22" (310 mm)
Length: 18.2" (462 mm)
Width: 4.5" (114.4 mm)

Concrete and Steel Fastener

Capacity: 42
Smooth Shank Diameter: .109"
Step Shank Diameter: .104"-.118"
Head Diameter: .250"
Range: ½" - 1½"
Shank Style: Smooth/Step
Finish: Zinc plated and black oxide
Collation: Standard washer style



For Fasteners see page 69 Concrete and Steel Collated Pins