

# SPECIFICATIONS

Model		<b>SSV65</b>		SSV75			
Type of operator station		Open CAB / <b>Closed CAB</b>		Open CAB / Closed CAB			
Engine	Model	V2607-CR-TE4		V3307-CR-TE4			
	Emission certification	Tier 4		Tier 4			
	Gross HP (SAE J1995)	HP (kW)/rpm	64.0 (47.7)/2700		74.3 (55.4)/2600		
	Net HP (SAE J1349)	HP (kW)/rpm	61.3 (45.7)/2700		71.6 (53.4)/2600		
	Displacement	cu.in. (cc)	159.7 (2615)		203.3 (3331)		
	Cylinders		4		4		
	Bore Stroke	in.(mm)	3.5 (87) × 4.4 (110)		3.8 (94) × 4.8 (120)		
	Aspiration		Turbocharged		Turbocharged		
Loader performance	Rated operating capacity-50% tipping load		lbs. (kg)	1950 (885)		2690 (1220)	
	Tipping load		lbs. (kg)	3900 (1770)		5380 (2440)	
	Breakout force	Bucket	lb. (kgf)	4839 (2195)		5884 (2669)	
		Lift arm	lb. (kgf)	3858 (1750)		4850 (2200)	
	Lift arm path			Vertical		Vertical	
Power train	Standard tire size			10-16.5-8PR		12-16.5-10PR	
	Chain size ASA#			80		100	
	Travel speed	Low	mph (km/h)	6.9 (11.1)		7.4 (11.9)	
		High	mph (km/h)	11.1 (17.8)		11.8 (19.0)	
	Traction force		lb. (kgf)	7339 (3329)		8494 (3853)	
	Ground clearance		in. (mm)	7.6 (193)		8.1 (207)	
Hydraulic system	Loader hydraulic flow		gpm (ℓ/min.)	18.0 (68.0)		20.9 (79.0)	
	Loader hydraulic pressure		psi (kgf/cm²)	3271 (230)		3271 (230)	
	Aux. hydraulic flow	Standard	gpm (ℓ/min.)	18.0 (68.0)		20.9 (79.0)	
		High	gpm (ℓ/min.)	28.0 (106.0)		30.4 (115.0)	
Service refill capacities	Hydraulic tank		gal. (ℓ)	4.2 (16.0)		4.2 (16.0)	
	Fuel tank		gal. (ℓ)	25.4 (96.0)		26.9 (102.0)	
Operating weight (Include operator weight 175 lbs.)			lbs. (kg)	6790 (3080) / <b>7055</b> (3200)		8157 (3700) / 8422 (3820)	

## DIMENSIONS

### **SSV65** / SSV75

