



[PRODUCTS](#) > [EXTENSION LADDERS](#) > [D6200-2 SERIES](#) > 32FT TYPE IA FIBERGLASS D-RUNG EXTENSION LADDER D6232-2

# 32FT TYPE IA FIBERGLASS D-RUNG EXTENSION LADDER D6232-2

★★★★☆ 3.3 | 8 Reviews

5 out of 8 (63%) reviewers recommend this product

222 questions and 223 answers for this product

[Write a review](#)

[Ask a question](#)





## VIDEOS



[BUY NOW](#)

**Style:** Multi-Section

**Size:** 32ft

**Type:** Type IA Duty Rating

[Resources](#) [Compatible Accessories](#)

The D6232-2 Fiberglass Two-Section 32ft Extension Ladder has non-conductive rails making this ladder ideal for working near electricity. With a duty rating of 300lb, the ladder is durable and long lasting. The exclusive Alflo® rung joint means Twist-Proof® performance on the job. The Traction-Tred® D rungs are slip-resistant and the side rails are interlocking. The dual action feet are for use on hard or penetrable surfaces and swivel easily. The base and fly sections separate easily to use the base section as a single ladder. The durable rail shield bracket and shoe help protect the bottom of the rail. The fly section rails are pre-pierced at the top for easy field installation of accessories.

## FEATURES

---

- Exclusive Alflo® rung joint means Twist-Proof® performance
- 1.63in slip-resistant Traction-Tred® D-rungs
- Smooth operating pulley with polypropylene rope
- Interlocking side rails with internal rail guides on bottom of fly section securely connect rails
- External guides at top of base section securely interlock rails
- Heavy duty extruded rung locks are spring loaded to operate smoothly
- Pre-pierced holes for easy field installation of accessories
- Base and fly separate easily to use base section as single ladder
- Combination rail shield bracket and shoe with SHU-LOK® and slip-resistant pad
- Molded rung braces on bottom step for increased durability
- Mar-resistant molded end caps

## SPECIFICATIONS

---

### DETAILS

<b>Style</b>	Multi-Section
<b>Size</b>	32ft
<b>Type</b>	Type IA Duty Rating
<b>Load Capacity</b>	300lb
<b>Material</b>	Fiberglass
<b>Certifications</b>	ANSI A14.5-2007, OSHA
<b>Werner Benefit</b>	Exclusive Alflo® rung joint means Twist-Proof® performance
<b>Unique Features</b>	Works Around Electricity
<b>Color</b>	Orange

Show Less

<b>Foot Design</b>	Shu-Lok ®, and spur plate
<b>Max. Load</b>	300lb
<b>Number of Sections</b>	2
<b>Rung Type</b>	D-Rung
<b>Section x Rungs</b>	2 x 16
<b>UPC</b>	051751019155

## DIMENSIONS

<b>Approx. Product Length (in)</b>	192
<b>Approx. Product Width (in)</b>	19
<b>Approx. Product Height (in)</b>	6.31
<b>Approx. Product Weight (lb)</b>	71.5
<b>Approx. Shipping Length (in)</b>	192
<b>Approx. Shipping Width (in)</b>	19
<b>Approx. Shipping Height (in)</b>	6.9
<b>Approx. Shipping Weight (lb)</b>	71.5
<b>Average Reach Height Extension Ladder (ft)</b>	31ft 7in
<b>Approx. Product Length (ft)</b>	16
<b>Approx. Closed Length (in)</b>	192
<b>Flange Dimension (in)</b>	1.19in
<b>Fly Width</b>	16in
<b>Max. Open Extended Height</b>	29ft
<b>Approx. Open Length (in)</b>	348
<b>Rails Dimension</b>	3.31in
<b>Rung Dimension</b>	1.625in
<b>Steps/Rung Dimension</b>	1.625in

## RESOURCES

---

[!\[\]\(74d4806277d7e73349d8e8c0897931e9\_img.jpg\) View D6200-2 Series Page](#)