



[Click Here To View](#)
[Item at](#)

www.GapPower.com

*Sales • Rentals
Parts & Service*

MS 441 C-M STIHL Magnum®

Professional Use



STIHL Magnum®

Series 1138

Professional Use

Featuring STIHL M-Tronic™ – an engine management control system that intelligently manages the operating performance of the engine – the MS 441 C-M STIHL Magnum® chain saw is ideal for professional jobs. The innovative system eliminates the low and high-speed carburetor adjustment screws and compensates for dirty air filters, changes in elevation and fuel quality through an electronic monitoring of the engine, digitally controlling the fuel/air mixture. Designed with the professional in mind, the MS 441 C-M STIHL Magnum™ features a side-access chain tensioner and an advanced anti-vibration system that helps reduce user fatigue. A translucent fuel tank makes checking levels easy. A decompression valve and pre-separation air filtration offer an easier start and longer run times.

Standard Features

- Features STIHL M-Tronic™ (M) – a new generation of Intelligent Engine Management that eliminates the low and high speed carburetor adjustment screws, compensates for dirty air filter, and changes in elevation and fuel quality
- Simplified warm start procedure
- Pre-separation air filtration offers longer run times
- Transparent fuel tank
- Side-access chain tensioner
- Decompression valve for easier starts
- Advanced anti-vibration system to help reduce operator fatigue

Specifications

DISPLACEMENT	70.7 cc (4.3 cu. in.)
ENGINE POWER	4.2 kW (5.6 bhp)
WEIGHT (powerhead only)	6.6 kg (14.6 lbs.)
FUEL CAPACITY	725 cc (24.5 oz.)
CHAIN OIL CAPACITY	360 cc (12.2 oz.)
OILOMATIC® CHAIN	3/8" RS3
RECOMMENDED RANGE OF GUIDE BAR LENGTHS	40 to 80 cm (16" to 32")

STIHL recommends #3624 (33 RS3 84) OILOMATIC® saw chain and 25" 3003 000 4030 STIHL ROLLOMATIC® E Super guide bar combination. The actual listed guide bar length can vary from the effective cutting length depending upon which power head it is installed.

IMPORTANT INFORMATION

WARNING! The occurrence called "kickback" can cause serious or fatal injury. Always read the instruction manual carefully before using your saw. STIHL uses a green and yellow color-coding system to help you select a powerhead, bar and chain combination that complies with the kickback requirements of ANSI Standard B175.1 (gasoline-powered saws) and §30 of UL 1662/ ANSI Standard B175.1 (electric chain saws). Ask your STIHL dealer about safe operating procedures and the advantages of the STIHL Quickstop® chain brake, STIHL Quickstop® Plus additional chain braking feature (Q), STIHL reduced kickback bars and STIHL low-kickback saw chains.

STIHL recommends the use of green reduced kickback bars and green low kickback chains on all STIHL chain saws.

Note: STIHL recommends use of fuel with no more than 10% Ethanol content. Using fuel with greater than 10% Ethanol content may cause damage to your equipment and may void your STIHL warranty. [Learn More...](#)

* The actual listed guide bar length can vary from the effective cutting length depending upon which power head it is installed.

WARNING! Improper use of any power tool may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your instruction manual before using such products.

STIHL products sold through U.S. STIHL dealers are for distribution in the United States only.